



MICRODUCT SUPPORT EQUIPMENT



SLMDT-648/54 SELF-LOADING MICRODUCT TRAILER

The Sherman & Reilly model SLMDT-648/54 Self-Loading Microduct Trailer is a tilt-bed design capable of handling combinations of small fiber count cables and microduct of six reels up to 48" in diameter by 27" wide x 2 reels and weighing up to 500 lb each. The reels are mounted two to a shaft, lifted to the top rail and simply rolled and locked into place at their relative storage position. Each reel rotates on bronze bushings for easy pull-off when using a **CABLEJET** system. Rim brakes are supplied to stop all six reels simultaneously. The top rail of the tilt-bed acts as an air reservoir that allows quick access for microduct pressurization. The unit can be powered by a 12 volt DC power unit or any of the power packs available for hydraulic **SUPERJET** operation. Standard equipment includes DOT lighting, adjustable front pintle eye, safety chains and hooks, toolbox, breakaway switch, and 12" x 2" electric road brakes.

SLRT-5696-8K SELF-LOADING REEL TRAILER

The SLRT-5696 open yoke design is self-loading with 10,500 lb. GVWR and handles reels up to 96" O.D. X 56" wide weighing 8,000 lbs. The 5696 features a manual hydraulic pump for lifting reels • automatic safety latches for reel transport • 2-5/8" reel shaft with oil impregnated bronze bushings • electric trailer brakes • manual front jack with pneumatic tire • Federal FMVSS 108 lighting • pintle eye and safety chains • options include overspin brake, power packs for hydraulic retriever and for hydraulic up and down, quick stop brake.



AC-10 AIR COOLER

The Sherman & Reilly Model AC-10 Air Cooler is a portable air to air after cooler used to cool compressor air when using the **CABLEJET** system in hot climates. The model AC-10 can cool the air to approximately 10°F over ambient. The cooling fan is driven by an air motor that uses a maximum of 50 CFM at 60 PSI and the total pressure drop is less than 3 PSI. Dimensions are 19" wide x 40" long x 24" high. Weight is 120 lb.



HYDRAULIC POWER PACK

Engine: Honda, 5 1/2 hp air cooled @ 4,000 rpm • Hydraulics: 3.5 gpm pump output, with 5 gallon reservoir and extension hoses • Dimensions: 31" x 18" x 25" (bare) 787mm x 457mm x 635mm (bare) • Bare Unit Weight: 120 lbs. / 55 kg. (including accessories) • Shipping Weight: 188 lbs. / 85 kg.