

Patent Pending

Push2Connect™



Airtight & Economical



Part # 7-053-004



ADVANTAGES:

- Ready to use
- Don't unscrew, just push duct to stop
- Collar for duct removal
- Air and water tight
- Cost effective and user friendly
- Proper installation visibility

GENERAL SPECIFICATIONS:

Maximum Burst Pressure	>300 psi
Maximum Sustained Pressure (15 minutes)	>300 psi
Maximum Air Pressure Pass Through	450 psi
Maximum Pull	>1500 lb
Duct Size	1-1/4" I.D., 1.66" O.D.

Other Sizes Available Soon!

All tests were completed in-house and with new material and U-Cups shown above. The test was conducted with a 1-1/4" SDR11 smoothwall pipe. The tests were conducted at 72 degrees fahrenheit temperature.

* Manufacturer reserves the right to make improvements. Dimensions, weights, and capacities are approximate. Manufacturer's specifications subject to change without notice.



Sherman & Reilly, Inc.

Revision #20091014

400 West 33rd St. • Chattanooga, TN 37410 USA • ISO 9001-2000
 Toll Free - 1.800.251.7780 • Phone - (423) 756-5300 • Fax - (423) 756-2948
 Internet - <http://www.sherman-reilly.com> • E-mail - sales@sherman-reilly.com