



SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - sales@sherman-reilly.com

HPLW-1004

HPLW-1004 Skid or Trailer Pilot Line Winder



The model HPLW-1004-S is a small compact skid mounted portable hydraulic powered 4-drum Pilot Line Winder/Puller. This unit is designed to also serve as a small distribution conductor puller that will develop a minimum of 1,000 lbs. line pull on top of each drum with 6,000 ft. of 3/8" diameter S&R "Sarlex" #12 single braid rope. Unit can be trailer, skid mounted, or pole trailer mounted and powered from line truck or any other suitable hydraulic power pack including portables. Performance is based on 15 GPM at 2,500 PSI for the full rated line pull and speed of 4 mph average to fill the drum. Each drum is equipped with aluminum-bronze disc payout brake with fine adjustments. Puller hydraulics is equipped with a holding valve to prevent dropping of the pilot rope and anti-rotation of drum. This unit is ideal and a labor saver when "framing the poles" and re-hauling the pilot ropes connected to the main pulling "bull rope" line. Puller can also be used to install small distribution class conductors under controlled conditions. Ropes are furnished in four different colors for ease of identification during stringing operations and installations. Dual hydraulic operated Levelwinds will allow operation to have precise control of placing ropes on to storage drums to prevent potential safety hazards that conventional leadscrew type levelwinds create. Operator involvement and alertness during stringing operations is essential for accident prevention and increased safety.

Toll Free 1.800.251.7780

ISO 9001 Certified



HPLW-1004

SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - sales@sherman-reilly.com



HPLW-1004 Skid or Trailer Pilot Line Winder



Specifications:

Rated line pull	1,000 lbs on top of drum
Line speed	4 MPH average to fill drum
Reel Capacity	6,000 ft. 3/8" Sarlex #12 single braid rope
Power pack output	2500 psi @ 15 GPM Top of Drum: 1,150 lb. line pull Bottom of Drum: 3,200 lb. line pull 2000 psi @ 15 GPM: Top of Drum: 900 lb. line pull Bottom of Drum: 2,450 lb. line pull

Skid Diminsions:

Length	65 in.
Width	92 in.
Height	4 ft. 6 in.
Net Weight w/ rope Skid only (approximate)	2,500 lb.

Skid mounted to Trailer Diminsions:

Length	11 ft. 6 in.
Width	8 ft.
Height	86 in.
Net Weight w/o rope (approximate)	
Net Weight w/ rope and trailer mounted (approximate)	6,700 lb.

* Dimensions, weights, capacities are approximate. Manufacturer's specifications subject to change without notice.



Toll Free 1.800.251.7780

ISO 9001 Certified