



SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - sales@sherman-reilly.com

6000 LB. PULLER

Model P-6048



Sherman & Reilly's "Smooth 6000," pulling at an average speed of 4 mph with an ultra quiet power plant, is ideal for heavy distribution or subtransmission construction. With 144,000 inch-pounds of torque, the P-6048 is powered by a 4cyl. diesel engine and equipped with S&R exclusive bronze payout brake operated from the control console.

Hydraulic front jack and rear leveling jacks are standard. Steel pulling drum has 8,500 ft. capacity of 3/4" rope and hydraulically driven telescope levelwind, standard. Trailer mounted on single axle, dual wheels, and operator's protective screen and seat equipped. The P-6048 is ideal as an extra strength intermediate size puller.

***All Equipment, Tools, and Accessories are Available
on Sherman & Reilly's Exclusive Lease/Purchase Plan.***



6000 LB. PULLER

SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - sales@sherman-reilly.com



Model P-6048 Puller



GENERAL SPECIFICATIONS*

Maximum Pulling or Capacity 144,000 in. lbs. of torque
(6,000 lbs. on top of drum)

Maximum Line Speed4 mph
(Average to fill drum)

Pulling Drum:

Size48 in. O.D. x 20 in. I.D.
x 38 in. T x 48 in. W

Rope Capacity8,500 ft. of 3/4" dia.
6,200 ft. of 7/8" dia.
12,000 ft. of 5/8" dia.

Maximum Reel:

Size72 in. dia. x 44 1/2 in. wide

Weight5,800 lbs.

Engine4 cylinder (diesel)

Drive SystemHydraulic (final stage
chain & sprocket)

Hydraulic System OilHyken Gold MV
Transmission Fluid

Emergency/Parking BrakeRatchet/PAWL (Pulling
mode Only)

Payout (Overspin) BrakeCaliper/ Disk

LevelwindHydraulic

TRAILER SPECIFICATIONS

AxleSingle

SuspensionLeaf Springs

BrakesElectric 12 1/4 in. x 3 3/8 in.

Tires7:50 x 16, 10 Ply

Front JackHydraulic

Adjustable Rear JackDrop leg & Pin Type (2)

Safety Chain & HooksTwo (2)

TowingAdjustable Pintle Eye

Trailer LightsStandard

LengthApprox. . .18 ft. 6 in.

WidthApprox.8 ft.

HeightApprox.9 ft.

WeightApprox. . .6,000 lbs.

*Dimensions, weights, capacities are approximate.
Manufacturer's specifications subject to change without
notice.

Note: Pulling drum, Reconducting reel and some
other options on PT-2766-BV and PT-3366 will fit the
P-6048 Puller.



Toll Free 1.800.251.7780

© Copyright 2000, Sherman & Reilly, Inc. Chattanooga, Tennessee

ISO 9001:2000 Certified