



# SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA  
Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948  
Web Site - <http://www.sherman-reilly.com> • E-Mail - [sales@sherman-reilly.com](mailto:sales@sherman-reilly.com)

Reel  
Winders

## RW-96/54-14K-D-T Reel Winder



### GENERAL SPECIFICATIONS:

Trailer mounted reel winder for re-conductoring and new conductor stringing applications with bi-directional operations. Powered by water cooled diesel engine, hydraulic drive self-contained with (Optional) Remote Frequency Hopping Spread Spectrum (FHSS) Radio System Technology Control. This system only requires one (1) operator to operate both V-Groove Puller Model P-1260-T and take-up reel winder in re-conductoring or new construction stringing applications. Reel winder to accommodate various sizes of take-up drums / reels of various materials (metal/wood/plastic) within the maximum dimensions unit will accommodate. Unit to accept Model RCR-60 Reconductor Reels, etc. Reel Winder with (Optional) FHSS Radio System Control will provide full operations of start-stop, PSI pressure setting and hydraulic levelwind all from P-1260-T Puller control console or any other remote area within 500 feet of control box mounted on reel winder. Unit can also be used as a separate drum puller in sub-transmission and distribution applications or as a reel tensioner behind multi-groove bullwheel tensioners, etc.

Toll Free 1.800.251.7780

ISO 9001 Certified





## RW-96/54-14K-D-T Reel Winder

### GENERAL SPECIFICATIONS:

Torque Rating .....	75,000 inch lbs., continuous
Line Speed .....	0 - 4 MPH
Engine .....	42 HP diesel, liquid cooled
Hydraulic Pump .....	Pressure compensated, 1.71 cu. in. piston pump
Brake .....	Spring applied, hydraulic released
Gearbox .....	Planetary, 25:1 ratio
Final Drive .....	Chain and Sprocket
Reel Capacity .....	96" x 54"
Reel Weight Capacity .....	14,000 lbs.

### TRAILER SPECIFICATIONS:

Weight, Approximate .....	6,000 lbs.
Gross Vehicle Weight Rating .....	20,000 lbs.
Length, Approximate .....	18 ft. 6 in.
Width, Approximate .....	8ft. 6in. (102")
Height, Approximate .....	10 ft. 9 in. (with 96" Reel)
Axle Rating .....	10,000 lbs. Tandem
Brakes .....	Air actuated ABS (optional) Electric (standard)
Front and Rear Jacks .....	Hydraulic controlled
Tow Hitch, adjustable .....	Pintle eye, minimum adjustment 22" to 34"
Safety Chains .....	Dual, 1/2" transport with safety hooks (or greater)
Lights .....	LED type, stop and turn signal lights each side (4 total)
Grounding Loops .....	5/8" copper clad (4)

\* Dimensions, weights, capacities are approximate. Manufacturer's specifications subject to change without notice.

