



# SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - [sales@sherman-reilly.com](mailto:sales@sherman-reilly.com)

**CON-  
DUCTOR  
REEL  
TRAILER**

## CRT-472-T Conductor Reel Trailer



The Sherman & Reilly Model CRT-472-T is a conductor reel trailer for transporting and tensioning four 72" x 52" conductor reels simultaneously with maximum rated weight capacity of 24,000 lbs. or maximum of 6,000 lbs. for each reel. Tension can be applied to all four reels during stringing operations. Each reel carrier equipped with Sherman & Reilly's exclusive 16" diameter ventilated aluminum-bronze brake disc for maximum cooling to prevent overheating during stringing operations, which could cause warpage and line surges during stringing. The disc will not rust and cause possible damage to the brake calipers. Each reel carrier is standard with quick release pillow block bearings.

The trailer is constructed of high strength steel tubing, continuously welded for rigidity and mounted on tandem axles. Adjustable front jack, adjustable leveling jacks on the rear, and D.O.T. sealed lighting are standard features. The pintle eye is fully adjustable with safety chains to match different heights of towing vehicles.



**CRT-472-T Cargo Reel Trailer**

**REEL CARRIER:**

Maximum Number of Reels	4
Maximum Reel Diameter	72 in.
Maximum Reel Width	52 in.
Maximum Allowable Weight	6,000 lbs. per Reel
Reel Shaft	2 <sup>5</sup> / <sub>8</sub> in. dia.
Reel Brake	16 in. dia. Aluminum Bronze Caliper/Disc (20" dia. optional) manual

**TRAILER:**

Overall Length	Approximate 33 ft.
Overall Width	Approximate 8 ft.-0"
Overall Height	Approximate 7 ft.-0"
Net Weight	Approximate 9,850 lbs.
Maximum GVWR	34,000 lbs.
Axles	Tandem or triple
Wheel size	17.5 x 6.75 HC
Tire size	215/75R17.5-H
Suspension	Leaf type
Road Brakes	Electric
Front Jack	1 drop leg screw type
Rear Jack	2 drop leg screw type
Lights	DOT 12 Volt
Towing	Adjustable Pintle Eye
Safety Chains and Hooks	2

**OPTIONS:**

Retriever	Hydraulic
Take up rewind (optional)	Manual
Underground option	Minimum of 6, each 4" diameter urethane lined, Bed rollers: Mounted on anti-friction ball bearings evenly spaced along bed to facilitate easier handling of underground conductors.
Gathering window:	3 urethane lined rollers mounted on anti-friction ball bearings located at trailer rear to serve as fairlead when paying out.

Other models also available for larger reels.

\*Dimensions, weights, capacities are approximate. Manufacturer's specifications subject to change without notice.

