



SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - sales@sherman-reilly.com

CARGO REEL TRAILER

CRT-6072-T All-Purpose Cargo Reel Trailer



The Sherman & Reilly Model CRT-6072-T is truly an all purpose, universal trailer ideal for day to day use in line construction. The 6,000 lbs. payload allows for conductor reels to be mounted on stand equipped with S&R's exclusive caliper, bronze ventilated disc brake assembly. Full cargo bed and large tool

box are all continuously welded high-strength steel with adjustable pintle eye, trailer brakes, D.O.T. lighting all standard. Design allows carrying poles to and from job site. Popular option is Hydraulic Retriever. Special paint available. Electric trailer brakes standard.

Other Cargo Trailers also available.

ISO 9001:2000 Certified

Toll Free 1.800.251.7780



CARGO REEL TRAILER

SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - sales@sherman-reilly.com



CRT-6072-T All-Purpose Cargo Reel Trailer

Optional Hydraulic Retriever allows for rewinding conductor. 'Quick release' couplings and hoses to fit truck PTO.



Hydraulic Retriever requires 2,500 PSI at 8 GPM. Develops 28,000 inch lbs. of torque.

GENERAL SPECIFICATIONS*

Maximum Payload	6,000 lbs.
Maximum Reel Diameter	72 in.
Maximum Reel Width	54 in.
Cargo Area	.64 in. wide x 102 in. long x 24 in. high
Crossarm Box	.20 in. wide x 36 in. long x 14 in. high
Tension Brake	Caliper / Disc 16 in. diameter Ventilated Bronze
Reel Shaft	.2 ⁵ / ₈ in. diameter
Overall Length	Approx. 16 ft.-0 in.
Overall Width	Approx. 8 ft.-0 in.
Overall Height	Approx. 6 ft.-0 in.
Height to Centerline of Reel	Approx. 5 ft.-4 in.
Maximum GVW	8,500 lbs.
Axle	Single
Suspension	Leaf Type
Tire Size	12 - 16.5 LT 10 Ply
Brakes	Electric (12 ¹ / ₄ " x 3 ³ / ₈ ") Front
Jack	Drop Leg & Screw Type (1)
Rear Jack	Drop Leg & Pin Type (2)
Lights	12 volt
Towing	Adjustable Pintle Eye
Safety Chains & Hooks	2
Hydraulic Retriever	Optional

*Dimensions, weights, capacities are approximate. Manufacturer's specifications subject to change without notice.



Toll Free 1.800.251.7780

ISO 9001:2000 Certified

© Copyright 2000, Sherman & Reilly, Inc. Chattanooga, Tennessee