



# SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - [sales@sherman-reilly.com](mailto:sales@sherman-reilly.com)

Reel Trailers

## SLDT-396/58-T Self-loading Duct Trailer



### General:

The Sherman & Reilly model SLDT-396/58 is a low profile self-loading duct trailer with a GVWR of 14,500 lb and the capability of handling three reels of innerduct 96" diameter x 58" wide and weighing up to 3,500 lb each. It employs a 12 volt DC power unit that operates a rear-mounted boom to lift and position the reels on the side-top rails. From there, they are manually rolled forward and locked into position for transport. The 2-1/2 inch diameter reel shaft is bronze bearing mounted for ease of operation and is fitted with a screw type reel lock to prevent the reels from rotating. Other features include electric trailer brakes with break-away switch, manual front jack with steel caster, safety chains, solar battery charger, federal FMVSS 108 lighting and an adjustable pintle eye.



## SLDT-396/58-T Self-loading Duct Trailer

### Specifications:

GVWR .....	14,500 lb
Maximum reel size .....	96" dia x 58" wide
Maximum reel weight.....	3,500 lb
Length .....	29'-10"
Width .....	102"
Height .....	74"
Weight .....	4,400 lb
Tire size .....	215/75R17.5H ply - 4 each
Wheel size .....	17.5 x 6.75 - 4 each
Trailer brakes .....	Electric
Axle size .....	8,000 lbs—2 each
Reel shaft size .....	2-1/2 dia, bronze bushing mounted
Front jack .....	Manual screw type
Power unit .....	12 volt DC with remote control
Safety chains and hooks .....	Standard
Adjustable pintle eye .....	Standard
Solar battery charger .....	Standard
Federal fmvss 108 lighting .....	Standard

### Optional equipment:

- 5.5 HP power pack in place of 12 volt power unit
- Tool box

\* Dimensions, weights, capacities are approximate. Manufacturer's specifications subject to change without notice.