



SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - sales@sherman-reilly.com

Self-Loading
Reel Trailers

SLRT-256/96-10K Self-Loading Reel Trailer



General Specifications:

The Sherman & Reilly Model SLRT-256/96-10K is self-loading and is open-yoke designed with a GVWR of 14,500 lbs. and the capability of handling (2) reels 96" OD x 56" wide and weighing up to 5,000 lbs. each. It employs a manually operated hydraulic pump to position the reels to a safe transporting height and has a unique pair of automatic safety latches to remove the load from the lift cylinders during transport. The 2-5/8" diameter reel shaft is bronze bearing mounted for ease of operation and can be fitted with an optional rim type brake/retriever for payout applications. Other features include electric trailer brakes, manual front jack with steel caster, safety chains, Federal FMVSS 108 lighting, break away switch and an adjustable pintle eye.

Options Available:

- Hydraulic up and down w/ 9 HP Hydraulic Power Pack
- Hydraulic up and down w/ 8 HP Hydraulic Power Pack
- Hydraulic Retriever
- Superjet Box Mount
- 12" Bronze Disc Payout Brake
- (Trailer must be 102" wide to accept 56" wide reels.)
- 102" Wide trailer to accept 62" reels or
- 56" wide reels with a bronze payout brake shaft
- Additional Shaft without brake

