

**SELF-
LOADING
REEL
TRAILER**

SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - sales@sherman-reilly.com



SLRT-3048-T Self-Loading Reel Trailer



The Sherman & Reilly Model SLRT-3048-T has the capability of self-loading and unloading a 48" O.D. reel full of conductor and carrying it to the job site. Loading features include all-hydraulic lifting for easy and smooth control of reel. Trailer is equipped with caliper disc payout brake for maximum control. Also equipped with adjustable stabilizing rear jacks, and adjustable pintle eye, all D.O.T. lighting standard. Other models available for larger reels.

**Other Self-Loading
Reel Trailers
also available**

GENERAL SPECIFICATIONS*

Maximum Reel Size 48 in.
Maximum Reel Weight 3,000 lbs.
Payout Brake Caliper Disc

TRAILER SPECIFICATIONS

Overall Length (approximate) 108"
Overall Width (approximate) 78"
Overall Height (approximate) 42"
Weight (approximate) 1,200 lbs.
Axle Single
CVWR Rating 5,500 lbs.
CAWR Rating 5,000 lbs.
Tire Size 8.75 - 16.5 LT (E)

*Dimensions, weights, capacities are approximate. Manufacturer's specifications subject to change without notice.



Toll Free 1.800.251.7780

ISO 9001:2000 Certified

© Copyright 2000, Sherman & Reilly, Inc. Chattanooga, Tennessee