



SHERMAN & REILLY

400 West 33rd St. • Chattanooga, TN 37410 USA

Toll Free 1.800.251.7780 • Phone 423.756.5300 • Fax 423.756.2948

Web Site - <http://www.sherman-reilly.com> • E-Mail - sales@sherman-reilly.com

SARLEX PULLING ROPE

SARLEX Pulling Rope



Sherman & Reilly Sarlex Pulling Rope is a single braid, 12-strand rope constructed of high tenacity polyester. Sarlex is always finished with a coating of polyurethane to optimize the ropes' abrasion life. Sarlex is also extremely easy to splice. The approximate elastic elongation of Sarlex is 3.7% @ the recommended working load. Available in 6 Colors: 4 basic colors are black, blue, red and green. Sizes available are:

OTHER SIZES AVAILABLE UPON REQUEST

Diameter Inches	Average Break Strength Pounds	Minimum Break Strength Pounds	Maximum Working Load 5:1 Pounds	Weight Pounds Per 100 Ft.
1/4"	2,500	2,250	500	2.0
5/16"	4,000	3,600	800	2.9
3/8"	6,000	5,400	1,200	3.9
7/16"	9,000	8,100	1,800	5.9
1/2"	12,500	11,250	2,500	8.5
9/16"	16,500	14,850	3,300	10.5
5/8"	18,200	16,380	3,640	11.8
3/4"	24,000	21,600	4,800	15.8
7/8"	35,500	31,950	7,100	23.6
1"	43,000	38,700	8,600	28.5

