



SHERMAN+REILLY®

P-2000X PULLER

20,000 LB. BULLWHEEL PULLER



- 1 Fully enclosed Safe-Zone® Cab with climate control.
- 2 Automatic horizontal floating levelwind for precise control.
- 3 Equipped with a 175 Hp industrial diesel engine.
- 4 Frame mounted tool box.
- 5 4 adjustable hydraulic leveling jacks.

FEATURES

- Pulling capacity of 20,000 lb.
- 23,000 ft. 20 mm anti-twist steel cable capacity.
- Fully hydraulic direct drive system.
- Equipped with CANbus technology and real-time self diagnostics.

SPECIFICATIONS

Pulling Capacity	Max: 20,000 lb. (Rated maximum)
Maximum Line Speed	Pulling: 4 mph
Controls	Digital with real-time tension monitoring and recording
Drum Dimensions	Core Diameter: 30 in. / Total Outside Width: 76 in. Inside Width: 50 in. / Flange Diameter: 76 in. (84 Optional)
Reel Capacity	0.84 in. dia. Unitrex™ 21,500 ft. 20 mm. dia. anti-twist Steel cable 23,000 ft.
Drive System	Twin 22 in. Bullwheels w/Direct Hydraulic Drive
Drive System Engine	Diesel, 175 Hp, water cooled, with Webasto Artic Pack
Fuel Capacity	12 gallon
Hydraulic Fluid	ISO Grade 32
Hydraulic Reservoir	20 gallon
Hydraulic Fluid Filtration	10 micron, both supply and return filters
Levelwind	Electrically-actuated, automatically-controlled
Operator's Safety Enclosure	Safe-Zone® Cab, fully-enclosed / single door
Frame Construction	Steel tubing
Length (Overall, Nom.)	26 ft. 10 in.
Width (Overall, Nom.)	8 ft. 6 in.
Height (Overall, Nom.)	11 ft. 3 in.
Weight*	42,640 lb. (With 20 mm dia. anti-twist rope)
GVWR	45,500 lb.
Suspension	Leaf-spring
Axle Configuration	Tri-axle
Wheel Configuration & Tires	Per Axle GAWR 15,000 lb. with tires 235/75 R17.5 @ 125 psi
Brakes (Trailer)	Electronic brakes w/anti-lock features
Towing Attachment	3 in. pintle eye, with two safety chains and hooks
Tie Downs	5/8 in. dia. Steel D-Strings (2)
Tongue Jack	Hydraulic, horizontal folding, with shoe
Bumper (SS/CS) Jacks	Hydraulic, vertical column, with shoe (2)
Battery	12 V, 720 CCA, BCI group 93 (2)
Electrical System	Split 12/24 VDC
Lights / Navigation	US DOT, LED, 12 VDC
Work Lights	Cab top floods
Grounding	3/4 in. dia. Copper-clad Steel ground loops (4)
Wheel Chocks	Standard
Fire Extinguisher	ABC
Color	S+R White

OPTIONS

Solar Battery Charger



P-2000X Puller in the field



P-2000X Puller featuring the Safe-Zone® Cab



P-2000X Puller in the field

*Specifications are subject to change