



SHERMAN+REILLY®

REEL TRAILERS

CRT-196/67 - ONE REEL | CRT-472/52 - FOUR REELS



- Conductor trailer built for transporting and tensioning.
- Equipped with an aluminum-bronze ventilated disc.
- Quick-release reel shaft bearings for easy and safe reel change.
- Available in a single reel and four-reel trailer configuration.

SPECIFICATIONS

CRT-196/67		CRT-472/52	
Maximum Reel Weight* (Dynamic)	20,000 lb., fully loaded, 3 in. reel shaft	Maximum Reel Weight*	6,000 lb. / Reel
Maximum Reel Size	96 in. OD x 67 in. wide	Maximum Reel Size	72 in. OD x 52 in. wide
Reel Shaft Diameter	2-5/8 in., 1 ea., and 3 in., 1 ea., included	Reel Shaft Diameter	2-5/8 in.
Reel Brake	20 in. dia. disc, Al-bronze	Reel Brake	16 in. dia. disc, Bronze
Brake Control	T-handle, manually adjusted	Brake Control	T-handle/Manual
Frame Construction	Steel tubing, continuous-weld	Frame Construction	Steel tubing, continuous-weld
Length, overall, nom.	16 ft. 8 in.	Length, overall, nom.	35 ft. 7 in.
Width, overall, nom.	8 ft. 6 in.	Width, overall, nom.	8 ft. 6 in.
Height, overall, nom.	9 ft. 4 in.	Height, overall, nom.	9 ft.
Weight*	6,500 lb.	Weight*	14,150 lb.
GVWR	30,000 lb.	GVWR	39,000 lb.
Suspension	Leaf-spring	Suspension	Leaf-spring
Axle Configuration	Tandem	Axle Configuration	Tandem
Wheel Configuration & Tires	Single, 215/75R17.5H	Wheel Configuration & Tires	Dual, 215/75R17.5-H, 10 bolt 6.75HC
Brakes, trailer	Electric	Brakes, trailer	Air
Tongue Jack	Drop-leg with pin & shoe	Tongue Jack	Manual
Bumper (SS/CS) Jacks	Drop-leg with pin & shoe, (2)	Bumper (SS/CS) Jacks	Manual
Towing Attachment	3 in. adjustable pintle eye	Towing Attachment	3 in. adjustable pintle eye
Safety Chains	2 ea., with hook	Safety Chains	2 ea. with hook
Lights / Navigation	US DOT, LED, 12 VDC	Lights / Navigation	US DOT, LED, 12 VDC
Grounding	3/4 in. dia. copper-clad steel ground loops, 4 ea.	Grounding	3/4 in. dia. Copper-clad steel grounding loops, 4 ea.
Paint	S+R White	Paint	S+R White
Height with 96 in. Reel	11 ft. 7 in.	Powerpack	13 Hp, hydraulic rewind *Hydraulic Retriever Performance: Approximately 20,000 in-lb at 7 GPM and 2,000 PSI. Do not exceed 12 GPM and 3,000 PSI.

OPTIONS

Hydraulic Front Jack
Rear Hydraulic Jacks
20 Hp Powerpack (engine Hp subject to availability)
RDG-2100 Rotating Distribution Ground
DG-4100 Running Ground
Air Brakes