



SHERMAN+REILLY®

SINGLE-REEL STATIONARY REEL STANDS

CRS-108/83 - 30,000 LBS. MAX CAPACITY | CRS-96/67 - 24,000 LBS. MAX CAPACITY



Constructed with structural-grade steel tubing

Coupled with a compatible tensioner, it can be hydraulically controlled by:

- Sherman + Reilly T-1608
- Sherman + Reilly T-2608
- Sherman + Reilly T-7212
- Sherman + Reilly PTR-7230
- Sherman + Reilly PTR-7240

Disc-caliper payout brake for controlled tail-tension

Quick-disconnect hydraulic fittings allow for rapid set up with purchase of Hydraulic Retriever Package

Anchor rings and grounding bars at each corner

SINGLE-REEL STATIONARY REEL STANDS

CRS-108/83 - 8,000 LBS. CAPACITY | CRS-96/67 - 20,000 LBS. CAPACITY

Sherman-Reilly.com

SPECIFICATIONS

	CRS-96/67-20k	CRS-96/67-24k	CRS-108/83-20k	CRS-108/83-30k
Maximum Reel Size:	96 in. OD x 67 in. wide	96 in. OD x 67 in. wide	108 in. OD x 83 in. wide	108 in. OD x 83 in. wide
Maximum Reel Weight:	20,000 lbs. static at full width	24,000 lbs. static at full width	20,000 static at full width	30,000 static at full width
Payout Brake:	Manual, 20 in. dia. disc. Aluminum-bronze	Manual, 20 in. dia. disc. Aluminum-bronze	Manual 20 in. dia. disc. Aluminum	Manual 20 in. dia. disc. Aluminum
Frame Configuration:	Reinforced truss on rectangular base	Reinforced truss on rectangular base	Reinforced truss on rectangular base	Reinforced truss on rectangular base
Frame Construction:	High-strength steel tubing	High-strength steel tubing	High-strength steel tubing	High-strength steel tubing
Length, overall, nom.:	10 ft., 10 in.	10 ft., 10 in.	11 ft., 11 in.	11 ft., 11 in.
Width, overall, nom.:	8 ft.	8 ft.	8 ft.	8 ft.
Height, overall, nom.:	6 ft., 2 in., without reel	6 ft., 2 in., without reel	6 ft., 5 in.	6 ft., 5 in.
Grounding:	3/4 in. dia. copper ground loops (4)	3/4 in. dia. copper ground loops (4)	3/4 in. dia. copper ground loops (4)	3/4 in. dia. copper ground loops (4)
Tie-Downs:	1 in. dia. Steel D-Rings (4)	1 in. dia. Steel D-Rings (4)	1 in. dia. Steel D-Rings (4)	1 in. dia. Steel D-Rings (4)
Paint:	S+R White	S+R White	S+R White	S+R White
Drive Bar Diameter:	2-5/8 in.	5 in.	3-15/16 in.	5 in.