




SHERMAN+REILLY®

P-1400X PULLER

14,000 LB. SINGLE DRUM PULLER



- 1** Lateral articulating drum engagement for rapid changing of drum.
- 2** Automatic horizontal floating levelwind for precise control.
- 3** Fully enclosed Safe-Zone® Cab with climate control.
- 4** Equipped with a 173 Hp Tier-4 Final Cummins industrial diesel engine.
- 5** Frame mounted tool box.
- 6** 3 hydraulic leveling jacks.

FEATURES

- Puller and reconductor in one unit.
- Pulling capacity of 14,000 lb.
- 15,000 ft. Unitrex™ synthetic rope capacity.
- Fully hydraulic direct drive system.
- CANbus technology and real-time self diagnostics.
- Optional RCR-54 Reel for reconductoring.

P-1400X PULLER

14,000 LB. SINGLE DRUM PULLER

Sherman-Reilly.com

SPECIFICATIONS

Pulling Capacity	14,000 lb. (Rated at the top of drum)
Maximum Line Speed	Pulling: 4 mph, Payout: 10 mph
Controls	Digital with real-time tension monitoring and recording
Drum Capacity	Core Diameter: 30 in. / Total Outside Width: 76 in. Inside Width: 64 in. / Flange Diameter: 54 in.
Drum Capacity	18 mm. dia. Unitrex™ 15,000 ft. 5/8 in. dia. Steel 15,000 ft.
Drum Weight (w/o rope)	w/ Standard Drum: 16,500 lb; w/ Reconductoring Reel: 15,300 lb
Drive System	Drum, with Direct Hydraulic Drive
Drive System Engine	Diesel, 173 Hp water cooled
Fuel Capacity	30 gallon
Hydraulic Fluid	ISO Grade 32
Hydraulic Reservoir	40 gallon, 32 usable gallons
Hydraulic Fluid Filtration (2)	10 micron, both supply and return filters
Levelwind	Hydraulically driven, automatically-controlled
Operator's Safety Enclosure	Safe-Zone® Cab, fully-enclosed / single door
Frame Construction	Steel tubing, steel plate
Length (Overall, Nom.)	22 ft. 8 in.
Width (Overall, Nom.)	8 ft. 6 in.
Height (Overall, Nom.)	9 ft. 8 in.
GVWR	27,000 lb.
Suspension	Leaf-spring
Axle Configuration	Tandem
Wheel Configuration & Tires	Single 245/70R 17.5
Brakes (Trailer)	Air brakes w/anti-lock feature on both axles
Towing Attachment	3 in. pintle eye, with two safety chains and hooks
Tie Downs	5/8 in. dia. steel D-Rings (2), 1 in. dia. steel D-Rings (2)
Bumper (SS/CS) Jacks	Hydraulic, horizontal folding, with shoe (2)
Tongue Jack	Hydraulic, vertical column, with shoe (1)
Electrical System	12 VDC
Battery	12 V, 720 CCA, BCI group 27
Lights / Navigation	US DOT, LED, 12 VDC
Grounding	3/4 in. dia. copper-clad steel loops (4)
Wheel Chocks	Standard
Fire Extinguisher	ABC
Color	S+R White

OPTIONS

RCR-54 Reel for reconductoring

Solar Battery Charger

SPECIFICATIONS

RCR-54 Reconductoring Reel	
Reel Capacity	10,000 lb. (of added conductor)
Reel OD	54 in.
Reel Width, outside	71.75 in.
Reel Width, inside transverse	63 in.
Reel Core Diameter	31.5 in. to 18.5 in.
Reel Weight*, nom.	1,890 lb.
Reel Hub Size	P-1400X Engagement Only
Reel Material	Steel, continuous-weld
T-Handle Wrench	Included
Lifting Tongs	Optional
Pulling Capacity	7,500 lb.



Rear view of the P-1400X Puller



P-1400X Control Panel