



SHERMAN+REILLY®

SINGLE-REEL STATIONARY REEL STANDS

CRS-108/83 – 30,000 LB. MAX CAPACITY | CRS-96/67 – 24,000 LB. MAX CAPACITY



CRS-96/67-20k



CRS-108/83-30k

Constructed with structural-grade steel tubing.

Coupled with a compatible tensioner, it can be hydraulically controlled by:

- Sherman + Reilly T-1608
- Sherman + Reilly T-2608
- Sherman + Reilly T-7212
- Sherman + Reilly PTR-7230
- Sherman + Reilly PTR-7240

Disc-caliper payout brake for controlled tail-tension.

Quick-disconnect hydraulic fittings allow for rapid set up with purchase of Hydraulic Retriever Package.

*Hydraulic Retriever Performance: Approximately 20,000 in-lb at 7 GPM and 2,000 PSI. Do not exceed 12 GPM and 3,000 PSI.

Anchor rings and grounding bars at each corner.

SINGLE-REEL STATIONARY REEL STANDS

CRS-108/83 - 8,000 LB. CAPACITY | CRS-96/67 -20,000 LB. CAPACITY

Sherman-Reilly.com

SPECIFICATIONS

	CRS-96/67-20k	CRS-96/67-24k	CRS-108/83-20k	CRS-108/83-30k
Maximum Reel Size	96 in. OD x 67 in. wide	96 in. OD x 67 in. wide	108 in. OD x 83 in. wide	108 in. OD x 83 in. wide
Maximum Reel Weight	20,000 lb. static at full width	24,000 lb. static at full width	20,000 static at full width	30,000 static at full width
Payout Brake	Manual, 20 in. dia. disc. Aluminum-bronze	Manual, 20 in. dia. disc. Aluminum-bronze	Manual 20 in. dia. disc. Aluminum	Manual 20 in. dia. disc. Aluminum
Frame Configuration	Reinforced truss on rectangular base	Reinforced truss on rectangular base	Reinforced truss on rectangular base	Reinforced truss on rectangular base
Frame Construction	Structural Tubing	Structural Tubing	Structural Tubing	Structural Tubing
Length, overall, nom.	10 ft. 10 in.	10 ft. 10 in.	11 ft. 11 in.	11 ft. 11 in.
Width, overall, nom.	8 ft.	8 ft.	8 ft.	8 ft.
Height, overall, nom.	6 ft. 2 in., without reel	6 ft. 2 in., without reel	6 ft. 5 in.	6 ft. 5 in.
Weight, overall, nom.	1,950 lb.	2,990 lb.	1,964 lb.	3,440 lb.
Grounding	3/4 in. dia. copper ground loops (4)	3/4 in. dia. copper ground loops (4)	3/4 in. dia. copper ground loops (4)	3/4 in. dia. copper ground loops (4)
Tie-Downs	1 in. dia. Steel D-Rings (4)	1 in. dia. Steel D-Rings (4)	1 in. dia. Steel D-Rings (4)	1 in. dia. Steel D-Rings (4)
Paint	S+R White	S+R White	S+R White	S+R White
Drive Bar Diameter	3-15/16 in.	5 in.	3-15/16 in.	5 in.

Hydraulic Retriever Performance:

Min. 25,000 in-lb (2,800 LB of line tension at 18 IN diameter)

NOTE: Some S+R products are equipped with a Retriever option
that is supported by external power source*

*Do not exceed 12 GPM and 3,000 PSI