



SHERMAN+REILLY®

SINGLE-REEL STATIONARY REEL STANDS

CRS-68/44 – 8,000 LBS. CAPACITY



- Constructed with structural-grade steel tubing

- Disc-caliper payout brake for controlled tail-tension

- Quick-disconnect hydraulic fittings allow for rapid set up with purchase of Hydraulic Retriever Package

- Anchor rings and grounding bars at each corner

SINGLE-REEL STATIONARY REEL STANDS

CRS-68/44 - 8,000 LBS. CAPACITY

Sherman-Reilly.com

SPECIFICATIONS

CRS-68/44	
Maximum Reel Size:	68 in. OD x 44 in. wide
Maximum Reel Weight:	8,000 lbs., fully static at full width
Payout Brake:	Manual, 20 in. dia. disc. Aluminum-bronze
Frame Configuration:	Reinforced truss on rectangular base
Frame Construction:	High-strength steel tubing
Length, overall, nom.:	5 ft.
Width, overall, nom.:	7 ft., 5 in. (including payout brake)
Height, overall, nom.:	4 ft., 6 in.
Grounding:	3/4 in. dia. copper ground loops (4)
Tie-Downs:	5/8 in. dia. Steel D-Rings (4)
Paint:	S+R White
Drive Bar Diameter:	2 5/8 in.

OPTIONS

RDG-2100 Rotating Distribution Ground
DG-4100 Running Ground
Hydraulic Retriever