




SHERMAN+REILLY®

# PLW-200E+ PILOT LINE WINDER

2,000 LB. FOUR DRUM ELECTRIC PILOT LINE WINDER



- 1 Safe-Zone® enclosure with Ocu-View™.
- 2 Remote Reel Engagement.
- 3 Ergonomic Control Panel with Adjustable Seat.
- 4 Synchronized Levelwind Control.
- 5 Light Bar, USB and 12V Charging.
- 6 10" touchscreen with embedded Know+Go Instructional Video System & a digital copy of the operator's manual.

## FEATURES

- 2,000 lb. Top of Drum Pulling Capacity.
- All-Electric Drivetrain.
- Automatic Battery Management.
- S+R Telematics™ provides real time support.
- Supports the installation of 4 conductors simultaneously.
- Independent roller assemblies designed for each of the four pilot lines.
- Single Drum Capacity: 6,000 ft. of 7/16 in. Rope.

# PLW-200 E+ PILOT LINE WINDER

2,000 LB. FOUR DRUM ELECTRIC PILOT LINE WINDER

Sherman-Reilly.com

## SPECIFICATIONS

<b>Maximum Pulling Capacity</b>	2,000 lb. rated at top of drum
<b>Max. Line Speed</b>	4.0 mph. top of drum
<b>Reel Capacity</b>	6,000 ft. of 7/16 in. PE-12 synthetic rope
<b>Drive System</b>	48 V Electric
<b>Charging time Standard Battery Size</b>	Rapid Recharge: 50% to 100% = ~1 hour; 0 to 100% = ~2 hours Wall Charger: Level 1 (120V): 4-5 hr for 0% to 50%; 8-9 hr for 0% to 100% Level 2 (240V): 2-3 hr for 0% to 50%; 4-5 hr for 0% to 100%
<b>Rapid Recharge System</b>	Diesel, Flywheel-Integrated Permanent Magnet Generator, 100A Field Charging
<b>Wall Charger Plug Type</b>	J1772 Plug
<b>Hydraulic Fluid</b>	ISO Grade 32
<b>Hydraulic Reservoir</b>	4 Gallons
<b>Payout Brake</b>	Manually controlled disc brakes, 12" diameter disc, bronze
<b>Levelwind</b>	Electric, joystick controlled (2)
<b>Operator's Safety Enclosure</b>	Safe-Zone® with Ocu-View™ open-air enclosure
<b>Frame Construction</b>	Steel tubing, continuous weld
<b>Length (overall, nom.)</b>	207 in. (17 ft. 3 in.)
<b>Width (overall, nom.)</b>	102 in.
<b>Height (overall, nom.)</b>	117 in.
<b>Weight (w/ rope)</b>	nominal 11,100 lb.
<b>GVWR</b>	12,000 lb.
<b>Suspension</b>	Leaf spring
<b>Axle Configuration</b>	Single
<b>Wheel Configuration and Tires</b>	Dual 235/85R 16LRG; 8-6.5
<b>Brakes (Trailer)</b>	Electric, with safety break-away switch and dedicated battery
<b>Towing Attachment</b>	3 in. pintle eye, with two safety chains and hooks
<b>Tie Downs (4)</b>	5/8 in. dia. steel D-rings
<b>Bumper (SS/CS) Jacks</b>	Hydraulic with galvanized shoe (2)
<b>Tongue Jack</b>	Hydraulic with galvanized shoe (1)
<b>Electrical System</b>	48/12 VDC

<b>Lights / Navigation</b>	US DOT, LED, 12 VDC
<b>Grounding (2)</b>	Two (2) grounding studs
<b>Wheel Chocks and Holders</b>	Standard
<b>Fire Extinguisher</b>	ABC
<b>Drum Covers</b>	Vinyl
<b>Color</b>	S+R white

## OPTIONS

<b>Tongue Extension</b>
<b>Solar Charger</b>
<b>Galvanized Finish</b>
<b>Additional Battery Size Options:</b> 15.375 kWh 20.5 kWh
<b>Air Brakes</b>
<b>J1772 Plug Adapters Available</b>

The PLW-200 E+ delivers all-electric operation with The Onboard Rapid Recharge System by S+R™, providing superior performance and automatic battery management so the operator can focus on the job at hand. With all the capabilities of our standard PLW-200H, the E+ has an all electric drivetrain designed to exceed all-day use. The On-Board Rapid Recharge System responds automatically, without input from the operator, until the work is done no matter how tough the job gets. In addition, S+R Telematics™ comes standard at no cost, providing industry leading support in real time. The E+ Series of products continues Sherman + Reilly's commitment to transform customer expectations for jobsite safety and equipment performance

