




SHERMAN+REILLY®

BWT-1363H HERITAGE TENSIONER

3,000 LB. 36 IN. BULLWHEEL TENSIONER



- 1 Safe-Zone® enclosure with Ocu-View™.
- 2 A set of 36 in. five-groove bullwheels with bolt-on cast linings.
- 3 Integrated reel carrier.
- 4 All stringing operations controlled from the safety of the Safe-Zone® enclosure.
- 5 Seamless reel change with Sherman + Reilly's pillow block bearing support.

FEATURES

- Tensioning capacity of 3,000 lb. for power in a compact configuration.
- Reel carrier accommodates reels up to 72 in. OD x 44.5 in. W and 6,500 lb.
- Two conductor keeper assemblies.
- Offset bullwheels and adjustable fairlead supports both LH and RH lay conductor.
- Available with hydraulic power pack for reel control, spider rewind, and hydraulic jack control.
- Also available with Pilot Line Spider® System (pictured).

BWT-1363H HERITAGE TENSIONER

3,000 LB. 36 IN. BULLWHEEL TENSIONER

Sherman-Reilly.com

SPECIFICATIONS

Tensioning Capacity	3,000 lb.
Maximum Line Speed	4 mph
Maximum Conductor Reel Size	72 in. OD x 44.5 in. wide
Maximum Conductor Reel Weight*	Dynamic over the road: 6,500 lb. Static jacks extended: 6,500 lb.
Reel Shaft Diameter	2.625 in.
Reel Supports	Sealed Ball Bearing, Quick Release
Payout Brake	16 in. diameter disc, bronze
Bullwheels	Nominal Diameter: 36 in. Bullwheel Count: 2 ea. Bullwheel Groove Count: 5 per Bullwheel Groove Lining: Replaceable Groove Radius: .75 in. Groove Depth: .75 in. Bottom of Groove Diameter: 33.98 in.
Tension Brake	27.75 in. diameter disc, bronze
Brake Control	3-axis caliper, manual Hydraulic, operated from Safe-Zone® enclosure
Fairlead Rollers	Supports LH and RH Lay
Operator's Safety Enclosure	Open-air Safe-Zone® enclosure
Frame Construction	Steel tubing
Length (Overall, Nom.)	17 ft.
Width (Overall, Nom.)	8 ft.
Height (Overall, Nom., Empty)	9 ft. 6 in.
Weight (Nom.)*	6,500 lb.
GVWR*	13,000 lb.
Suspension	Leaf-spring
Axle Configuration	Single Axle - Single Wheel
Per Axle GAWR	12,000 lb. with tires 235/75R17.5 @ 125 psi
Brakes (Trailer)	Electric, with safety break-away switch
Towing Attachment	3 in. adjustable pintle eye
Safety Chains	2 each, with hooks
Bumper (SS/CS) Jacks	Manual drop and pin (2)
Tongue Jack	Manual 2-speed crank jack
Electrical System	Split 12 VDC

Backup Battery	12V
Lights / Navigation	US DOT, LED, 12 VDC
Grounding	1 in. grounding stud (1) Grade 5H
Deck Cover	Non-slip Surface
Wheel Chocks	Standard (2)
Fire Extinguisher	ABC
Color	S+R White

OPTIONS

Full vinyl cover
Bullwheel only cover
Payout brake cover
PowerPack option including hydraulic jacks, hydraulic retriever, and Spider® Pilot Line System with independent levelwind.
PowerPack option including hydraulic jacks, and hydraulic retriever
Air Brakes
Galvanized Finish Available
RDG-2100 Rotating Distribution Ground
DG-4100 Running Ground
12 V solar battery charger



BWT-1363H cab interior.