

MODEL NO. 9511

FEATURES

- Designed for stringing overhead ground wire.
- Frame is high strength aluminum alloy.
- Sheaves mounted on anti-friction ball bearings are available with polished aluminum.

MATERIALS

SIZE, IN.	POLISHED GROOVE	DUCTILE IRON	URETHANE
6	x	x	х
8	х	x	х
12	х		Х

COMPLETE SPECIFICATIONS

	OUTSIDE SHEAVE DIA. IN.	RIM WIDTH IN.	TOTAL OVERALL HEIGHT IN.	HOOK THICKNESS IN.	THROAT HEIGHT IN.	THROAT WIDTH IN.	HANGING LENGTH IN.	OVERALL WIDTH IN.	GROOVE RADIUS IN.	HOOK HEIGHT IN.	HOOK WIDTH IN.
SIZE	A	В	С	D	E	F	G	Н		J	К
6	6	1 1/2	4 1/2	27/32	1 13/16	1 1/2	11 1/8	4 1/4	7/16	3 31/32	31/32
8	8	1 3/4	6 1/2	1 7/16	2 3/16	1 3/4	15 11/32	4 3/4	7/16	6 7/8	1 3/4
12	12	2	10	7/16	2 1/2	1 3/4	20	4 3/4	19/32	6 7/8	1 1/2



