

## GROUND TO AIR AND HANDLINE BLOCKS

### FEATURES

- Two Models Available: GTA-358 (closed side) & HLB-472 (open side).
- Ideal for handline purposes.
- Constructed of lightweight, high strength aluminum alloy for maximum strength at minimum weight.
- Ideal with synthetic ropes.
- Rope size for both models: 3/8 in. - 5/8 in.



### SPECIFICATIONS

MODEL NO.	ROPE SIZE IN.	LENGTH IN.	WIDTH IN.	WEIGHT LB.	MWL LB.
GTA-358	3/8-5/8	7	2 1/2	2.9	2,000
HLB-472	3/8-5/8	6 3/16	2 1/4	2.3	1,250

## ALL PURPOSE SNATCH BLOCK MODEL NO. 4841

### FEATURES

- For all types of rope including wire rope.
- Wide groove sheaves for ropes up to 1 1/4 in. in diameter.
- Aluminum-magnesium alloy frame, ductile iron sheave, forged steel safety hook.
- Sheave has 360° guard built into frame.
- Wide upper frame makes block self aligning when used in other than vertical position.
- Excellent hoisting block, particularly for pole top application due to light weight and high strength features.
- Works well with transformer gin.



### SPECIFICATIONS

4841	
Sheave Size	61/2" O.D. x 2 1/8" Rim Width
Hook Opening	1 1/2 in.
Maximum Rope Diameter	1 1/4 in.
Bearing Type	Ball Bearings
Throat to Top of Sheave	8 3/4 in.
Weight	18 1/2 lb.
Max Working Load	6000 lb.
Overall Length	17 in.

4841

\*Specifications are subject to change