



SHERMAN+REILLY®

MODEL NO. 9511

MODEL NO. 9511

FEATURES

- Designed for stringing overhead ground wire.
- Frame is high strength aluminum alloy.
- Sheaves mounted on anti-friction ball bearings are available with polished aluminum.

MATERIALS

| SIZE, IN. | POLISHED GROOVE | DUCTILE IRON | URETHANE | MAXIMUM WORKING LOAD LIMIT |
|-----------|-----------------|--------------|----------|----------------------------|
| 6 | X | X | X | 3000 LB. |
| 8 | X | X | X | 5000 LB. |
| 12 | X | | X | 8000 LB. |

COMPLETE SPECIFICATIONS

| | OUTSIDE SHEAVE DIA. IN. | RIM WIDTH IN. | TOTAL OVERALL HEIGHT IN. | HOOK THICKNESS IN. | THROAT HEIGHT IN. | THROAT WIDTH IN. | HANGING LENGTH IN. | OVERALL WIDTH IN. | GROOVE RADIUS IN. | HOOK HEIGHT IN. | HOOK WIDTH IN. |
|------|-------------------------|---------------|--------------------------|--------------------|-------------------|------------------|--------------------|-------------------|-------------------|-----------------|----------------|
| SIZE | A | B | C | D | E | F | G | H | I | J | K |
| 6 | 6 | 1 1/2 | 4 1/2 | 27/32 | 1 13/16 | 1 1/2 | 11 1/8 | 4 1/4 | 7/16 | 3 31/32 | 31/32 |
| 8 | 8 | 1 3/4 | 6 1/2 | 1 7/16 | 2 3/16 | 1 3/4 | 15 11/32 | 4 3/4 | 7/16 | 6 7/8 | 1 3/4 |
| 12 | 12 | 2 | 10 | 7/16 | 2 1/2 | 1 3/4 | 20 | 4 3/4 | 19/32 | 6 7/8 | 1 1/2 |

