



SHERMAN+REILLY®

CRT-196/67 | CRT-472/52

Reel Trailers (One-Reel & Four-Reel)



CRT-196/67



CRT-472/52

- 1 Conductor trailer built for transporting and tensioning
- 2 Equipped with an aluminum-bronze ventilated disc brake
- 3 Quick-release reel shaft bearings for safe and easy reel changes
- 4 Available in a single-reel or four-reel configurations

Specifications

CRT-196/67

Max. Reel Weight (Dynamic)	20,000 lb. fully-loaded, 3 in. reel shaft
Max. Reel Size	96 in. OD x 67 in. wide
Reel Shaft Diameter	2½ in.; 1 ea. & 3 in.; 1 ea. included
Reel Brake	20 in. dia. disc, aluminum-bronze
Brake Control	T-handle, manually-adjusted
Frame Construction	Steel tubing, continuous-weld
Length (Overall, Nom.)	16 ft. 8 in.
Width (Overall, Nom.)	8 ft. 6 in.
Height (Overall, Nom.)	9 ft. 4 in.
Weight*	6,500 lb.
GVWR	30,000 lb.
Suspension	Leaf-spring
Axle Configuration	Tandem
Wheel Configuration & Tires	Single, 215/75R 17.5H
Brakes (Trailer)	Electric
Tongue Jack	Drop-leg w/ pin & shoe
Bumper (SS/CS) Jacks	Drop-leg w/ pin & shoe (2)
Towing Attachment	3 in. adjustable pintle eye
Safety Chains	2 ea. w/ hook
Lights/Navigation	US DOT, LED 12 VDC
Grounding	¾ in. dia. copper-clad steel ground loops (4 ea.)
Color	S+R white
Height w/ 96-in. Reel	11 ft. 7 in.

Options

- Hydraulic front jack
- Rear hydraulic jacks
- 20 HP powerpack (engine HP subject to availability)
- RDG-2100 rotating distribution ground
- DG-1400 running ground
- Air brakes

CRT-472/52

Max. Reel Weight (Dynamic)	6,000 lb./reel
Max. Reel Size	72 in. OD x 52 in. wide
Reel Shaft Diameter	2½ in.
Reel Brake	16 in. dia. disc, bronze
Brake Control	T-handle/manual
Frame Construction	Steel tubing, continuous-weld
Length (Overall, Nom.)	35 ft. 7 in.
Width (Overall, Nom.)	8 ft. 6 in.
Height (Overall, Nom.)	9 ft.
Weight*	14,150 lb.
GVWR	39,000 lb.
Suspension	Leaf-spring
Axle Configuration	Tandem
Wheel Configuration & Tires	Dual, 215/75R 17.5 H, 10-bolt 6.75HC
Brakes (Trailer)	Air
Tongue Jack	Manual
Bumper (SS/CS) bJack	Manual
Towing Attachment	3 in. adjustable pintle eye
Safety Chains	2 ea. w/ hook
Lights/Navigation	US DOT, LED, 12 VDC
Grounding	¾ in. dia. copper-clad steel grounding loops (4 ea.)
Color	S+R white
Powerpack	13 HP, hydraulic rewind *Hydraulic retriever performance: approx. 20,000 in.-lb. at 7 GPM and 2,000 psi. Do not exceed 12 GPM and 3,000 psi