

## Model XS-200

- XS-200 contains two identical sheaves
- Designed for uplift conditions and can be used either in suspension or on a crossarm
- Side gate positively locks with spring plunger
- Available shackle for hold down rope (order separately)
- Maximum working load of 2,500 lb.; block weight 16 ¼ lb.
- Available in polished groove, nylon or urethane



XS-200

## Accessories

### Adjustable Insulator Adapter

- Two models available: AIA-CF and AIA-J
- Used for reconductoring on vertical tie-top post insulators
- Compatible with glass and ceramic insulators only; do not use with polymer insulators
- AIA-CF adjusts to fit most insulators with neck dia. for 2 7/8 - 3 1/2 in.
- AIA-J adjusts to fit most insulators with neck dia. for 3 1/4 - 4 7/8 in.
- Fits all Sherman+Reilly XS-100-B stringing blocks



AIA-CF

### Horizontal Line Post Adapter

- Model: LPA-17-A
- Used with horizontal line posts
- Fits in the insulator cap and is held securely in place with the bolt, which is provided for securing the conductor clamp
- This enables accurate sagging and minimizes handling and lifting of conductor during clipping-in operation
- Permits placing block at 30° for negotiating angles



LPA-17-A

### Grounding Stud

- Provides location to ground block



Grounding Stud

### 1210 Adapter

- Designed for hanging aerial cable blocks directly to messenger for mid-span support. Will fit any Sherman+Reilly stringing blocks equipped with socket connector
- Accommodates up to 5/8 in. wire



1210 Adapter