



SHERMAN+REILLY®

# P-2000X Puller

## 20,000-lb. Bullwheel Puller



- 1 Fully-enclosed Safe-Zone® cab with climate control
- 2 Automatic horizontal floating levelwind for precise control
- 3 Equipped with a 175 HP Tier-4 final industrial diesel engine
- 4 Frame-mounted tool box
- 5 Four adjustable hydraulic leveling jacks

### Features

- Pulling capacity of 20,000 lb.
- 23,000 ft. 20 mm anti-twist steel cable capacity
- Fully-hydraulic direct drive system
- Equipped with CAN bus technology and real-time self diagnostics

## Specifications

<b>Max. Pulling Capacity</b>	20,000 lb.
<b>Max. Line Speed</b>	Pulling: 4 mph
<b>Controls</b>	Digital w/ real-time tension monitoring & recording
<b>Drum Dimensions</b>	Core dia.: 30 in. Total outside width: 76 in. Inside width: 50 in. Flange dia.: 76 in. (84 in. optional)
<b>Reel Capacity</b>	0.84 in. dia. Unitrex™: 21,500 ft. 20 mm dia. anti-twist steel cable: 23,000 ft.
<b>Drive System</b>	Twin 22 in. bullwheels w/ direct hydraulic drive
<b>Drive System Engine</b>	Diesel, 175 HP, water-cooled w/ Webasto arctic pack
<b>Fuel Capacity</b>	12 gal.
<b>Hydraulic Fluid</b>	ISO Grade 32
<b>Hydraulic Reservoir</b>	20 gal.
<b>Hydraulic Fluid Filtration</b>	10 micron, both supply & return filters
<b>Levelwind</b>	Electrically-actuated, automatically-controlled
<b>Operator's Safety Enclosure</b>	Fully-enclosed, climate-controlled Safe-Zone® cab
<b>Frame Construction</b>	Steel tubing
<b>Length (Overall, Nom.)</b>	26 ft. 10 in.
<b>Width (Overall, Nom.)</b>	8 ft. 6 in.
<b>Height (Overall, Nom.)</b>	11 ft. 3 in.
<b>Weight*</b>	42,640 lb. (w/ 20 mm dia. anti-twist rope)
<b>GVWR</b>	45,500 lb.
<b>Suspension</b>	Leaf-spring
<b>Axle Configuration</b>	Tri-axle
<b>Wheel Configuration &amp; Tires</b>	Per axle GAWR 15,000 lb. w/ tires 235/75 R17.5 @125 psi
<b>Brakes (Trailer)</b>	Electronic brakes w/ anti-lock features
<b>Towing Attachment</b>	3 in. pintle eye w/ (2) safety chains & hooks
<b>Tie Downs</b>	½ in. dia. steel D-rings (2)
<b>Tongue Jack</b>	Hydraulic, horizontally-folding w/ shoe
<b>Bumper (SS/CS) Jacks</b>	Hydraulic, vertical column, w/ shoe (2)
<b>Electrical System</b>	Split 12/24 VDC
<b>Battery</b>	12V, 720 CCA, BCI group 93 (2)

<b>Lights/Navigation</b>	US DOT, LED, 12 VDC
<b>Work Lights</b>	Cab-top floods
<b>Grounding</b>	¾ in. dia. copper-clad steel ground loops (4)
<b>Wheel Chocks</b>	Standard
<b>Fire Extinguisher</b>	ABC
<b>Color</b>	S+R white

## Options

- Solar battery charger



P-2000X Puller



P-2000X Safe-Zone® Cab



P-2000X