



SHERMAN+REILLY®

P-6000H Heritage Puller

6,000-lb. Pulling Capacity



- 1 Safe-Zone® enclosure with Ocu-View™ screen
- 2 All stringing operations controlled from the safety of the Safe-Zone® enclosure
- 3 Chain drive; single hydraulic motor, Penta-drive coupling system with remote engagement
- 4 Helicopter-ready payout brake
- 5 Manual jacks standard on bumper (2) and tongue (1); hydraulic jack option available

Features

- Capable of pulling 6,000 lb. on a 62 in. diameter reel
- Maximum line speed of 6 mph
- Drum capacity: up to 15,500 ft. of ¾ in. PE-12 or 25,000 ft. of ½ in. Ultrex™
- Ratchet dog failsafe brake

Specifications

Max. Pulling Capacity	6,000 lb. rated at 30 in. from drum center
Min. Tensioning Capacity	1,250 lb. at top of drum/3,500 lb. at core
Max. Line Speed	Pulling: 6 mph; tensioning: 30 rpm
Mechanical Payout Brake	27.75 in. bronze disc, helicopter-ready
Reconductoring Reel Size	72 in. dia./45 in. width
Max. Reel Weight	Dynamic - over the road: 6,400 lb. Static - jacks extended: 11,000 lb.
Drum Dimensions	Core dia.: 24 in. Total outside width: 36 in. Flange dia.: 62 in.
Drum Capacity	Up to 15,500 ft. of ¾ in. PE-12 or 25,000 ft. of ½ in. Ultrex™
Drive System	Chain drive: single hydraulic motor, Penta-drive coupling system w/ remote engagement
Drive System Engine	Turbocharged, Tier-4 final, diesel, 116 HP, water-cooled Kubota®
Fuel Capacity	30 gal.
Hydraulic Fluid	ISO Grade 32
Hydraulic Reservoir	25 gal. (32 usable gal.)
Hydraulic Fluid Filtration	10 microns, return filter
Levelwind	Hydraulically-driven, Steady-Rest™ controlled directional change
Operator's Safety Enclosure	Safe-Zone® open-air enclosure
Frame Construction	Steel tubing, steel plate, continuous weld
Length (Overall, Nom.)	20 ft. 6 in.
Width (Overall, Nom.)	8 ft. 6 in.
Height (Overall, Nom.)	9 ft. 4 in.
Weight	13,410 lb. w/o rope 15,765 lb. w/ rope & drum
GVWR	20,500 lb.
Axle Configuration/ Suspension	Tandem/leaf-spring
Wheel Configuration & Tires	Single 235/75R 17.56 LJR
Brakes (Trailer)	Electric w/ break-away switch & visual indicator for battery charge state
Towing Attachment	3 in. pintle eye w/ (2) safety chains & hooks
Tie Downs	(4) 1 in. dia. steel D-rings
Bumper (SS/CS) Jacks	Single-speed drop, pin, crank
Tongue Jack	Two-speed drop, pin, crank

Battery/Electrical System	(2) 12V/810 CCA/Group 27
Lights/Navigation	US DOT, LED 12, VDC
Grounding	Grade 5H (2)
Wheel Chocks	Standard (2)
Fire Extinguisher	ABC
Color	S+R white

Options

- Hydraulic jacks
- Light bar w/ 12V accessory option
- Air axle
- Tongue extension
- Solar battery charger
- Galvanized finish available
- 72 in. x 45 in. RCR reel
- Know+Go instructional video system



Streetside of P-6000H Heritage Puller