



SHERMAN+REILLY®

# RW-90/56-30K

## Single-Reel Reel Winder



- 1 Accommodates reels of up to 90 in. OD x 56 in. wide
- 2 Multi-adjust levelwind for reel widths and cable sizes with manual levelwind release
- 3 Direct-drive eliminates chain drive
- 4 Oil-free hydraulic bleed button for easy hose installation
- 5 Toolless, quick reel removal with pin-free X-change™ drive
- 6 Balanced lifting bells for smooth operation and eliminating the risk of uncontrolled loads

## Specifications

|                                  |                                                                  |
|----------------------------------|------------------------------------------------------------------|
| Maximum Reel Size (inches)       | 90 in. O.D. x 56 in. wide                                        |
| Maximum Reel Weight (lbs.)       | Over the road: 10,000 lbs.<br>Site use (full-width): 30,000 lbs. |
| Failsafe Brake                   | Manual-hydraulic                                                 |
| Shaft Diameter (inches)          | Standard: 4 in.<br>Optional: 5 in. (adapter provided)            |
| Frame Construction               | Steel tubing, continuous-weld                                    |
| Length x Width x Height (inches) | 143 in. L x 101 in. W x 106 in. H; overall nominal               |
| Grounding                        | Bronze ground stud (1)                                           |
| Tie-Downs                        | D-rings, 1 in. dia. steel, 4 each                                |
| Lifting Points                   | Four (4) rated lifting points for transport of empty unit        |
| Fork Tubes                       | For transporting empty unit on non-motor side                    |
| Paint                            | S+R white                                                        |

## Options

- 16mm x 25,000 ft with ø 90" x 56" reel
- 18mm x 22,000 ft with ø 90" x 56" reel
- 22mm x 22,000 ft with ø 90" x 56" reel
- ø 90" x 56" reel
- RCR-90 reconductoring reel

| Optional RCR-90 Reconductoring Reel |                                     |
|-------------------------------------|-------------------------------------|
| Reel Capacity                       | 30,000 lb.                          |
| Reel OD                             | 90 in.                              |
| Reel Width (outside)                | 56 in.                              |
| Reel Width (inside transverse)      | 45 in.                              |
| Reel Core Diameter                  | 34-25 in.                           |
| Reel Weight (nom.)                  | 1,212 lb.                           |
| Reel Hub Size                       | Accommodates 3-15/16 in. reel shaft |
| Reel Material                       | Steel, continuous-weld              |