



SHERMAN+REILLY®

# RW-90/56-30K

## Single-Reel Reel Winder



- 1 Accommodates reels of up to 90 in. OD x 56 in. wide
- 2 Multi-adjust levelwind for reel widths and cable sizes with manual levelwind release
- 3 Direct-drive eliminates chain drive
- 4 Oil-free hydraulic bleed button for easy hose installation
- 5 Toolless, quick reel removal with pin-free X-change™ drive
- 6 Balanced lifting bells for smooth operation and eliminating the risk of uncontrolled loads

## Specifications

Maximum Reel Size (inches)	90 in. O.D. x 56 in. wide
Maximum Reel Weight (lbs.)	Over the road: 10,000 lbs. Site use (full-width): 30,000 lbs.
Failsafe Brake	Manual-hydraulic
Shaft Diameter (inches)	Standard: 4 in. Optional: 5 in. (adapter provided)
Frame Construction	Steel tubing, continuous-weld
Length x Width x Height (inches)	143 in. L x 101 in. W x 106 in. H; overall nominal
Grounding	Bronze ground stud (1)
Tie-Downs	D-rings, 1 in. dia. steel, 4 each
Lifting Points	Four (4) rated lifting points for transport of empty unit
Fork Tubes	For transporting empty unit on non-motor side
Paint	S+R white

## Options

- 16mm x 25,000 ft with ø 90" x 56" reel
- 18mm x 22,000 ft with ø 90" x 56" reel
- 22mm x 22,000 ft with ø 90" x 56" reel
- ø 90" x 56" reel
- RCR-90 reconductoring reel