



SHERMAN+REILLY®

TRT-184 | TRT-284 | TRT-384

Turret Reel Trailers (One, Two, Three-Reel)



- 1 360° rotational range with reel mount on turret
- 2 Capable of independently orienting the direction of payout without having to reposition the trailer
- 3 Rotating turret may be locked at 15° intervals
- 4 Quick-release reel shaft bearings for safe and easy reel changes
- 5 Turret may be removed to use trailer for transporting equipment
- 6 Options include: hydraulically-driven retriever, electric-hydraulic payout brake, hydraulic front jack, hydraulic outriggers, gathering window with bed rollers and more

Specifications

	TRT-184/60 (one reel)	TRT-284/60 (two reels)	TRT-384/60 (three reels)
Max. Reel Weight	7,000 lb.	7,000 lb. per reel; 14,000 lb. total	Electric brake: 7,000 lb. per reel; 21,000 lb. total Air brake: 8,000 lb. per reel; 24,000 lb. total
Max. Reel Size	84 in. OD x 60 in. wide	84 in. OD x 60 in. wide each	84 in. OD x 60 in. wide each
Reel Shaft Diameter	2 5/8 in.	2 5/8 in.	2 5/8 in.
Tensioning Brake	16 in. dia. disc, bronze	16 in. dia. disc, bronze	16 in. dia. disc, bronze
Turret Rotation Range	360°; lockable in 15° increments	360°; lockable in 15° increments	360°, lockable in 15° increments
Frame Construction	Steel tubing, continuous-weld	Steel tubing, continuous-weld	Steel tubing, continuous-weld
Length (Overall, Nom.)	13 ft. 4 in.	21 ft. 6 in.	30 ft. 11 in.
Width (Overall, Nom.)	8 ft.	8 ft. 4 in.	8 ft. 6 in.
Height (Overall, Nom.)	8 ft. 9 in. (w/o reel)	8 ft. 8 in. (w/o reel)	9 ft. (w/o reels)
Weight*	4,600 lb. (w/o conductor or reel)	6,750 lb. (w/o conductor or reel)	Electric brake: 10,170 lb. (w/o conductor or reel) Air brake: 14,320 lb. (w/o conductor or reel)
GVWR	12,000 lb.	21,000 lb.	Electric brake: 33,800 lb. Air brake: 38,500 lb.
Suspension	Leaf-spring	Leaf-spring	Leaf-spring, heavy-duty
Axle Configuration	Single	Tandem	Tandem
Wheel Configuration & Tires	Single, 235/75R 17.5	Single, 215/75R 17.5	Dual, 215/75R 17.5H
Brakes (Trailer)	Electric w/ break-away switch	Electric w/ break-away switch	Electric w/ safety break-away switch or air
Tongue Jack	Manual or hydraulic w/ shoe	Manual or hydraulic, w/ shoe	Manual or hydraulic, w/ shoe
Tie-Downs	D-rings (1 ea. at platform corners)	D-rings (4 ea., 2 per side)	D-rings (4 ea., 2 per side)

Standard Features

Towing Attachment	3 in. adjustable pintle eye
Safety Chains	2 ea. w/ hook
Lights/Navigation	US DOT, LED, 12 VDC
Grounding	3/4 in. dia. copper-clad steel loops (4 ea.)
Color	S+R white

Options

- Electric-over-hydraulic payout brakes
- Hydraulic retriever (min. 25,000 in.-lb.; 2,800 lb. of line tension at 18 in. dia. - DO NOT EXCEED 12 GPM and 3,000 psi) NOTE: Some S+R products are equipped w/ retriever option that is supported by an external power source
- 20 HP powerpack (engine HP subject to availability)
- Hydraulic front jack
- Hydraulic outrigger jack (TRT-384/60-24K)
- Gathering window and bed rollers
- RDG-2100 rotating distribution ground
- DG-4100 running ground
- Solar battery charger

*Specifications are subject to change